1640ECOMPACT LOADERS





KEY FEATURES


- ✓ Ultra-Compact Skid Loader
- ✓ ROPS/FOPS Level II
- ✓ Dual T-Bar Control System
- ✓ Audible Back-Up Alarm
- ✓ Standard High Back Cushion Seat
- Lightweight for Easy Transport

KEY SPECIFICATIONS

- Operating capacity (50%) 386 kg (850 lbs.)
- Overall height to top of ROPS 1897 mm (74.7")
- ✓ 909 mm (35.8") maximum width less bucket
- ✓ Gross Power 18.1 kW (24 hp) @ 2400 rpm
- ✓ Yanmar / 3TNV82A-BPMSR / Stage V Compliant
- √ 86 Nm (68 ft.-lbs.) @ 1200 rpm max torque
- ✓ 2438 mm (96") height to hinge pin
- ✓ 1352 kg (2,980 lbs.) operating weight

METRIC

		METRIC
CAPACITIES	Operating Capacity At 50% Tipping Load	386 kg
	Operating Weight	1351.70 kg
	Tipping capacity	711.10 kg
WEIGHT AND DIMENSIONS	Wheelbase	775 mm
	Overall Operating Height - Fully Raised	3167 mm
	Height to Hinge Pin - Fully Raised	2438 mm
	Overall Height to top of ROPS	1897 mm
	Dump angle at full height	46 °
	Dump height	1836 mm
	Overall length with bucket	2576 mm
	Dump reach - Full height	376 mm
	Rollback at ground	30 °
	Seat to ground height	879 mm
	Overall width less bucket	909 mm
	Bucket Width	914 mm
	Ground clearance	150 mm
	Overall length - Less Bucket	1905 mm
	Clearance Radius - Front with Bucket	1473 mm
	Rear departure angle	23 °
PERFORMANCES	Travel speed (unladen)	8.90 km/h
WHEELS	Standard tires	8.70 x 12
ENGINE	Engine brand	Yanmar
	Engine model	3TNV82A-BPMSR
	Engine norm	Stage V
	Max. torque / Engine rotation	86 Nm / 2400 rpm
	Power source	Diesel
	Engine power (Hp / kW)	24.47 Hp / 18.10 kW
	Battery voltage	12 V
	Starter	1.70 kW
HYDRAULICS	Standard flow - Auxiliary hydraulics	38.20 l/min
TANK CAPACITIES HYDRAULICS	Fuel	29 I
	Hydraulic tank capacity	27.30
	Displacement	1.30







One Gehl Way, West Bend, WI 53095 Phone: (262) 334-9461

