

### MASTERS EVERYDAY TASKS

#### Main brush Ø 640 mm with different trims

The bema 30 Dual PowerMaster guarantees best sweeping results when used in agriculture, road construction and industry.

And it performs day after day. The smallest model of the PowerMaster range is also equipped with an internal motor. Thanks to a wide variety of extensive optional equipment the sweeper is extremely versatile.

## **FEATURES**

#### ✓ Automatic adjustment:

The 3D roller level compensation and the optional swivel joint balance effortlessly any unevenness.

# ✓ Manages of large amounts of dirt:

Collection container with a large volume.

## Reliable thanks to central control and durable thanks to internal motors:

The Hydroblock contains all of the hydraulic control and safety elements such as an overpressure valve, overrun protection of the main brush, a switching valve for the collection container "Dual" and connection options for the rotary side bruhes. The premium version including flow control valve (up to 220 l/min), a load sensing system and an additional electric 2-way valve is optionally available.

#### ✓ Flexible use, thanks to the Dual system:

Fast and easy switching between free sweeping and collecting dirt, no changeover time required.

## ✓ Optimally equipped for every application:

Equipment of the sweeper according to customer requirements.

#### **CARRIER VEHICLES**



Wheel loader



Telehandler



Yard loader



Unimog truck



Forklift



Tractor front/rear

#### **OPTIONAL EQUIPMENT**



Water spray unit main brush, rotary side brushes



Rotary side brush with bema SideControl



Mechanical drive incl. drive shaft



Hydraulic lateral movement 500 mm to the left/right



Hydraulic swivel device 20° to the left/right



Scraper unit
without collection container



High-pressure water unit 120 bar or 50 bar



bema Control from 3 functions available



bema 30 Dual PowerMaster attached on Unimog with rotary side brush and hydraulic lateral movement (500 mm to the left/right)



bema 30 Dual PowerMaster attached on wheel loader, collection container Dual opened





bema 30 Dual PowerMaster without collection container with bema scraper unit (see page 58/59)

## **TECHNICAL DATA**

Machine type Working width	bema 30 Dual PowerMaster			
	1850 mm	2050 mm	2300 mm	2600 mm
Drive	Hydraulic drive, powerful Gerotormotor with drive shaft Ø 32 mm completely inside (heavy series).  Optional mechanical drive incl. drive shaft			
Minimum hydraulic power of the carrier vehicle	35 l/min			
Weight basic machine excl. special equipment (approx.)	295 kg	340 kg	390 kg	445 kg
Volume / weight (approx.) collection container Dual	340 l / 150 kg	380 I / 160 kg	430 l / 165 kg	480 l / 175 kg
Main brush Ø 640 mm	PPN or snow brush PPN, optional steel/PPN mixture brush, steel flat wire/PPN mixture brush. Toolless and stepless adjustment of the main brush via adjustment spindle			
Brush speed	Recommended 100 to 150 rpm			
Wheels	Super-elastic wheels Ø 250 x 80 mm (railsafe)			
Rotary side brush Ø 600 mm (optional equipment)	Hydraulic drive including bema SideControl (comfort operation, combines 3-way valve and speed controller), rotary side brushes are available for the right and/or left side, Selectable brushes: PPN, steel/PPN, steel flat wire/PPN, steel flat wire, weed trim			
Water spray unit (optional equipment)	200/400 litres water tank, tank filter and 12/24 volts pressure pump (direct injection of water into the main brush and rotary side brushes)			

Further attachments and equipment, as well as special constructions on request. Technical data and weight measurements are approximate and non-binding. Weight measurements without special equipment and attachment. Mistakes and errors reserved. © bema GmbH Maschinenfabrik (2021.10)

# **FEATURES IN DETAIL**



Premium-Hydroblock (optional) and bema SideControl



Rotary side brush for gutters, curbstones and building borders



3D roller level compensation and optional swivel joint