

RT195 - NEW

COMPACT LOADERS



KEY FEATURES

- ✓ Multiple Track Widths and Tread Patterns
- ✓ IdealTrax™ Auto Tensioning System
- ✓ Pilot Operated Joystick Controls
- ✓ High-Flow Auxiliary Hydraulics Available
- ✓ Swing-out Cooler

KEY SPECIFICATIONS

- ✓ 2,787 lbs. (1264 kg) Rated Operating Capacity (50%)
- ✓ 69.3 hp (51.7 kW) Yanmar Engine 4TNV98C-NMS2, Stage IV
- ✓ 120" (3048 mm) Height to Hinge Pin
- ✓ 69" (1749 mm) Overall Machine Width Less Bucket
- ✓ 78" (1979 mm) Overall Height to top of ROPS

		METRIC
CAPACITIES	Operating Weight	3810 kg
	Unladen weight	3422 kg
	Operating Capacity at 35% Tipping Load	884.50 kg
	Operating Capacity At 50% Tipping Load	1264 kg
	Tipping capacity	2527 kg
WEIGHT AND DIMENSIONS	Overall Operating Height - Fully Raised	4018 mm
	Height to Hinge Pin - Fully Raised	3048 mm
	Dump reach - Full height	648 mm
	Dump angle at full height	39 °
	Overall length with bucket	3279 mm
	Departure angle	27 °
	Carry Position	226 mm
	Ground clearance	188 mm
	Overall width less bucket	1746 mm
	Bucket Width	1778 mm
	Clearance Radius - Front with Bucket	2063 mm
	Track Rollers	3
ENGINE	Engine brand	Yanmar
	Engine model	4TNV98C-NMS2V
	Engine power (Hp)	68.40 Hp
	Engine power (kW)	51 kW
	Max. torque / Engine rotation	241 Nm @ 2500 rpm
	Battery voltage	12 V
	Accessory plug	120 V
	Alternator - Ampere	100 A
TRANSMISSION	Transmission type	Hydrostatic
HYDRAULICS	Standard flow - Auxiliary hydraulics	70 l/min
	Auxiliary Hydraulic Pressure	224 bar
	High-Flow Auxiliary Hydraulics - Option	120 l/min
	High-Flow Auxiliary Hydraulics Pressure - Option	200 bar
TANK CAPACITIES	Hydraulic tank capacity	36 l
	Fuel	58.70 l
	Cooling liquid	12.90 l
	Number of cylinders	4
NOISE AND VIBRATION	Noise to environment (LwA)	101.40 dB
	Noise at driving position (LpA)	82 dB
	Whole-Body Vibration (ISO 2631-1)	1.10 m/s²

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



STANDARD FEATURES

- Brake Control (Auto / Manual)
- Cup Holder
- Hydraloc™ Safety System
- Anti-Vandalism Protection
- Lift Arm Support Device
- Integral Access Plate (removable)
- ROPS/FOPS Level II Overhead Guard
- All-Tach® Attachment Mounting System
- Front and Rear - Work Lights
- Horn
- 12Volt Power Port
- IdealTrax® automatic track tensioning system
- Operator Restraint Bar
- Pilot Joystick Controls
- Two-Speed Drive
- Auxiliary Hydraulics
- High-Back Adjustable Seat
- Hydrostatic Drive - Servo

OPTIONAL FEATURES

- Air Conditioning
- Air Ride Suspension Seat
- Suspension Seat - Mechanical
- Power-A-Tach® Attachment Mounting System
- Sound reduction Package
- Engine Block Heater
- Hydraglide™ Ride Control
- High-Flow Auxiliary Hydraulics
- Cabin with Heat
- Back-Up Alarm
- Cab Enclosure
- Selectable Self-Leveling Hydraulic Lift Action 4



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT