

VT230

COMPACT LOADERS

GEHL®



KEY FEATURES

- ✓ Color Display with Keyless Start + Security Code
- ✓ IdealTrax™ Auto Tensioning System
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for More Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Dual Flange Idlers - Front + Rear
- ✓ Pilot Joystick Controls
- ✓ Backup Alarm

KEY SPECIFICATIONS

- ✓ Operating Capacity (35%) - 1043 kg (2,300 lbs.)
- ✓ Overall height to top of ROPS - 2045 mm (80.5")
- ✓ Gross Power - 53.7 kW (72 hp)
- ✓ 294 Nm (217 ft.-lbs.) @ 1800 rpm max torque
- ✓ 3073 mm (121") height to hinge pin
- ✓ 1753 mm (69") machine width - less bucket
- ✓ 4196 kg (9,250 lbs.) operating weight

METRIC		
CAPACITIES	Operating Weight	4196 kg
	Operating Capacity at 35% Tipping Load	1043.26 kg
	Operating Capacity At 50% Tipping Load	1490.50 kg
WEIGHT AND DIMENSIONS	Overall Operating Height - Fully Raised	4064 mm
	Height to Hinge Pin - Fully Raised	3073 mm
	Dump reach - Full height	940 mm
	Dump angle at full height	42 °
	Overall Height to top of ROPS	2045 mm
	Overall length with bucket	3589 mm
	Ground clearance	191 mm
	Overall width less bucket	1753 mm
	Clearance Radius - Front with Bucket	2235 mm
ENGINE	Engine brand	Yanmar
	Engine model	4TNV98CT-XNGL
	Engine power (Hp)	72.82 Hp
	Engine power (kW)	53.30 kW
	Max. torque / Engine rotation	294 Nm @ 1800 rpm
	Battery voltage	12 V
	Alternator - Ampere	100 A
HYDRAULICS	Standard flow - Auxiliary hydraulics	86.50 l/min
	Auxiliary Hydraulic Pressure	239.59 bar
	High-Flow Auxiliary Hydraulics - Option	114 l/min
	High-Flow Auxiliary Hydraulics Pressure - Option	229.25 bar
TANK CAPACITIES	Hydraulic tank capacity	22.70 l
	Fuel	143.80 l
	Cooling liquid	18 l
	Displacement / Number of cylinders	3.30 l / 4

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



STANDARD FEATURES

- Engine Auto-Shutdown System
- Hydraglide™ Ride Control
- Rear Lights
- Single Flange Front/Dual Flange Rear Idlers
- Anti-Vandalism Protection
- IdealTrax® automatic track tensioning system
- LED Work Lights
- 12Volt Power Port
- Pilot Joystick Controls
- Brake Control (Auto / Manual)
- All-Tach® Attachment Mounting System
- Foot Throttle
- Battery Disconnect
- Engine Block Heater
- Hand throttle
- 4 point lift
- Hydrostatic Drive - Servo
- High-Back Adjustable Seat
- Integral Access Plate (removable)
- Two-Speed Drive

OPTIONAL FEATURES

- Bluetooth car radio
- Sliding Side Windows
- IdealAccess™ Fold-Up Door
- Rearview Camera
- Counterweight
- Cab Enclosure
- Suspension Seat - Mechanical
- Inner rear view mirror
- Swing-out Cab Door
- Suspension Seat - Air Ride



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT